

TECHNICAL DATA SHEET

Silicone Spray



Reduces Friction

Provides a waterproof, low friction coating to protect the applied area. Suitable for silicone-friendly surfaces. When used in areas such as door seals, It does not harden the cords. That allows stopping noise and dust from entering.

TECHNICAL DATA

■ Type	Aerosol Spray
■ Color	Translucent
■ Odor	Caracteristic
■ Flash Point (°C) (min)	<0°C
■ Density	0,80-0,90 g/cm3

APPLICATIONS AREAS

- Vehicle door seals, door hinges, hatch covers, conveyors, textile machinery (including sewing needles)

HAZARD PHRASES

- H222: Extremely flammable aerosol.
- H280: Contains gas under pressure; may explode if heated.
- H304: May be fatal if swallowed and enters airways. H315: Causes skin irritation.
- H336: May cause drowsiness or dizziness. H319: Causes serious eye irritation.
- H411: Toxic to aquatic life with long lasting effects. Precautionary Statements (P): P281: Use personal protective equipment as required.
- P405: Store locked up.
- P501: Dispose of contents / container in accordance with local / regional / national / international regulations P302+P352 IF ON SKIN: Wash with plenty of soap and water. P362: Take off contaminated clothing and wash before reuse.
- P251: Pressurized container: Do not pierce or burn, even after use.
- P410+P403: Protect from sunlight. Store in a well-ventilated place.
- P280: Wear protective gloves / protective clothing/ eye protection / face protection.
- P261: Avoid Breathing Dust / fume / gas / mist / vapours / spray.
- P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P403+P233: Store in a well-ventilated place. Keep container tightly closed.
- P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.

DIRECTIONS FOR USE

1. Provide adequate ventilation.
2. Shake can thoroughly before use. Note: There is no ball agitator inside the can. For best results, aerosol can should be at room temperature before spraying.
3. Holding can 8 to 10 inches from the surface for open area lubrication, or 5 inches using the extension tube provided for hard to reach areas, press the nozzle and discharge the product on the assembly.

STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8C to 21C unless otherwise labeled. Optimal storage is at the lower half of this temperature range.

PACKAGING (Volume)

400 ml Aerosol Can (box of 24 pieces)

